



Fact Sheet

PostBase[®] Vision Auto A7



Marble White Cover

Features

- Easy to use large, 5" color touchscreen
- Motorized, tilting display for best viewing angle
- Automatic envelope processing at up to 70 letters/minute
- SealCheck envelope sealing security
- Sealing status light indicator
- 7kg. Capacity integrated postal scale
- Differential weighing for integrated scale
- Rate wizard for postal products
- Automatic postal rate updates
- Integrated postage tape dispenser for parcels
- MoCA Parcel Shipping Software
- Secure PIN protection
- 20 Customizable rate shortcuts
- 8 Standard, 30 custom printable envelope graphics
- Up to 30 custom printable envelope graphics
- Create up to 12 different printable text messages or QR codes to promote your mail
- Received stamp for incoming mail
- Easiest ink replacement with on-screen guidance
- Connected to MyFP Customer Portal for easy mailing system management

Options & Upgrades

- Large platform external USB scale up to 30 kg
- Vision360 online postal analytics and reporting for up to 250 cost accounts

Specifications

- Dimensions: 37"(L) x 16"(D) x 11.3-12.9"(H)
- Expandable Catch Tray Length: 12.6"-17.5"
- System Weight: 26.67 kg.
- Catch Tray Weight: 1 kg.
- Envelope Sizes: 4" x 6" - 10" x 14"
- Maximum Envelope Thickness: .40"
- Noise Emission: <70 dB(A)

Connectivity

- High-Speed LAN or Built-in Wi-Fi

Supplies

- Certified FP Postal Inkjet Cartridge
- Postage Meter Strip Tapes
- SEALIT Envelope Sealing Fluid

Postal Security Device (PSD/Meter)

- Canada Post Approved Meter
- FIPS 140-2 Level 3 Cryptography Certified

Manufacturing & Certifications

- Manufactured: Wittenberge, Germany
- ISO-9001, 14001, 45001, 50001, 27001
- CE, GS, CSA, Nemko, UL Listed
- Complies with FCC Part 15, Subpart B, Class B

Energy Consumption & Conservation

- Operating Energy Consumption: 80W
- Standby Energy Consumption: 7W
- Switched Off Energy: 0.5W
- Electrical Requirements: 100-240V/2.0A/50-60Hz
- Energy Star[®] 3.0 Certified

